

# Acrylastic 810 White Mastic



## Properties / Specifications

### Color:

White, tan, or gray

### Solids by volume:

60% Min.

### Viscosity:

Buttering grade

### Elongation:

500%

### Tensile strength:

500psi

### Shelf life:

24 months min.

### Weight per gallon:

9.6 lbs

### Tack free:

1 hour

### Coverage:

20 square feet per gallon or 60 lineal feet at 4 inch wide application

### V.O.C

<50 g/L

***Tough, Durable, Ultra Elastic. Wide Range of Compatibility. Easy to Apply.***

Davlin Coatings *Acrylastic* Mastic 810 is an extra tough, flexible, tenacious, and durable white mastic membrane, based on Davlin's world renowned *Capseal* formula.

*Acrylastic* 810 is user friendly and can be applied using a brush, putty knife, or trowel, and its high pigment level provides superior hiding power.

***Surface Preparation:*** Surface must be dry and free of oil, particulate, rust, or other debris.

***Application:*** Do not apply if temperature is below 50°F or above 110°F. Do not apply if there is a threat of rain or dew within 48-72 hours. Apply eighth inch to surfaces to be treated. Can be applied to laps, cracks, seams, directional wall changes, screw heads, roof intrusions, flashings, etc. Cures by evaporation. Cure time affected by temperature and humidity variables.

***Cleanup:*** If compound is still wet, clean up with warm soapy water.

***Storage:*** In a clean, warm and well-ventilated area. Storage area temperature must be above 45°F.

***Precautions:*** Be sure the lid is tight and the pail is secured to avoid spillage in transport. Keep from freezing. Do not heat container or store at temperatures greater than 150°F. Keep out of reach of children. Close container after each use. Do not take internally! If swallowed, do not induce vomiting. Call physician immediately.

The information, ratings and opinions stated above are, to the best of our knowledge, accurate, representing the results of laboratory and field evaluation. It is presented in good faith to assist the user in determining whether our products are suitable for his application. Since the user's application and other requirements are not known by us or are beyond our control, no warranty or guarantee as to results is hereby made or implied by Davlin Coatings, Inc.

Davlin Coatings LLC  
700 Allston Way  
Berkeley Ca 94710 USA  
(800) 709-5919  
www.davlincoatings.com

made in the USA  
designed by Davlin in California

© 2015 Davlin Coatings