

# RESTORE, REJUVENATE,

and Extend the Life of Your Asphalt Shingles With

# 100 RR SHINGLE SEAL





# 100 RR SHINGLE SEAL

## PHYSICAL PROPERTIES

<b>COLOR:</b> STANDARD AND CUSTOM COLORS	<b>VOC:</b> <0.37 LB/GAL
<b>COMPONENTS:</b> 1	<b>PERCENT NON VOLATILE:</b> 30%
<b>VISCOSITY:</b> 52-58 KREBS	<b>WEIGHT PER GALLON:</b> 8.5LBS
<b>FLASH POINT (SETA):</b> >215 F	<b>CURING MECHANISM:</b> AIR DRY
<b>COVERAGE PER GALLON:</b> 200SQ/FT	<b>COATS:</b> 1-2
<b>PENETRATION:</b> NO. 52 WHATMAN, INCHES MIN 1	

### Product Description:

100 RR SHINGLE SEAL is a waterborne emulsion developed to prolong the life of asphalt shingles. It provides lasting weather protection for both old and new roofs, inhibits algae growth and reduces granule loss.

### Product Use:

100 RR SHINGLE SEAL is primarily used to protect and extend the life of asphalt composition shingles.

### Product Advantages:

100 RR penetrates and has excellent adhesive qualities to minimize granule loss.  
100 RR is easy to apply with airless, roller or brush.  
100 RR is water-based for easy clean-up and low odor.  
Clear 100 RR dries clear and will not change the color of shingles.

### Packaging:

100 RR SHINGLE SEAL is available in one (1) and five (5) gallon pails, 55 gallon drums, and 265 gallon totes.

### Surface Preparation:

All surfaces must be clean, free of dirt, algae, mildew and other contaminants.

### Application Procedure:

Stir 100 RR SHINGLE SEAL thoroughly until uniformly blended. Avoid excessive mixing to prevent air entrapment. Thinning is not recommended.

Spray, Brush or Roll saturating entire surface.

Drying time to recoat at 70 °F. 50% RH : 2 hours

Clean equipment with water or water and detergent immediately after use.

### Product Limitations:

Do not apply during or 24 hours preceding inclement weather including rain, fog, mist or freezing temperatures.

Keep Material from freezing

The information, ratings, and opinions stated above are, to the best of our knowledge, accurate, representing the results or laboratory and field evaluation. It is presented in good faith, to assist the user in determining whether our products are suitable for his application. Since the user's application and other requirements are not known by us or are beyond our control, no warranty or guarantee as to results is hereby made or implied by Davlin Coatings LLC.